



## OutDECO Panel Care Instructions

### General Care & Finish

- **Natural Aging:** Untreated panels develop a silvery-gray patina, similar to aged teak, and remain water/termite resistant.
- **Color Preservation:** To keep the dark color, apply an exterior water-based solid stain or sealer as you would for a deck, re-applying periodically.
- **Painting:** Panels can be painted directly, as the factory stain acts as a primer.

### Cleaning

- **Mild Dirt:** Hose down with cold water and use a soft brush with mild soap, then rinse thoroughly.
- **Stubborn Stains/Mildew:** Use a solution of 5 parts water to 1 part bleach, apply with a cloth, rinse well, and air-dry.
- **Application:** Treat stains quickly; avoid saturating the panel.

### Key Points

- OutDECO panels are designed for outdoor use and do not *require* finishing for material integrity.
- Always test new finishes in an inconspicuous area.



### 10-Year Material Warranty & Minimum Installation Requirements

OUTDECO USA panels carry a Material Warranty of 10 Years.

10 YEAR WARRANTY covers OUTDECO USA panels against material rot, bloat or delamination under normal outdoor atmospheric and moisture "run-off" conditions.

Installations are the responsibility of the installer. These directions must be followed for the warranty to be valid.

OUTDECO USA's hardwood panels must be mounted in a vertical plane, and must not be submerged or in constant contact with water, soil, or chemicals.

Material Warranty valid within USA and Canada.

The benefits to the consumer given by this warranty are in addition to and not in conflict with all other rights and remedies of the consumer under a law in relation to the goods or services to which the warranty relates.