KLEEN ZYMES

USDA LIQUID BACTERIA & ENZYME

- LIVE BACTERIA WITH 3-WAY ACTION
- SAFE * NON-TOXIC * NON-ACID
- DIGESTS & LIQUIFIES ORGANIC WASTES
- COUNTERACTS BAD ODORS

A synergized three way action bacteria culture with enzymatic action on grease, soils, vomit, spilled food and other organic wastes. Formulated with a powerful odor counteractant for complete removal of bad odors! Highly resistant to disinfectants & freechlorine. The solution in non-polluting and non-toxic. The bacteria is non-pathogenic and certified salmonella free. Please note below the variety of uses for this product. You will find many more!

WHERE:

SCHOOLS*HOSPITALS*MUNICIPALITIES*
CONTRACTORS*HOTELS&MOTELS*RESTAURANTS*INDUSTRIAL PLANTS*OFFICE
BUILDINGS

FOR:

GREASE TRAPS * ODOR CONTROL * CARPET CLEANING * PORTA-TOILETS * SEPTIC TANKS * RECREATIONAL VEHICLES * WET WELLS * DOWN PIPES

INSTRUCTIONS

GENERAL ODOR CONTROL Eliminate odors caused by vomit, spoiled foods, decomposed animals, animal waste in garbage cans, waste receptacles, locker rooms, carpet, etc. Spray product directly on odors and allow the bacteria to ingest the material & the fragrance to dispel odors. CARPETS: Spot clean and vacuum carpet thoroughly. Mix « pint per gallon of water. Apply with sprayer. Keep moist at least 30 minutes. Repeat if odor persists. EQUIPMENT: Use « to 1 pint per gallon of mixed cleaners for extraction, bonnet, or brush or other method. GREASE TRAPS: For traps less than 20 cubic feet, add 4-5 oz. (for larger traps use 8-10 oz.) of product daily, to a sink or pipeline closest to the trap. Do this at night or when the traps are used the least. After adding, flush down with a cup of lukewarm water. PORTA-TOILETS: Add 1 gallon directly and cover the solids with water to aid digestion. Each time toilet is pumped, start treatment again with 1 gallon of product. SEPTIC TANKS: Add 1 pint per 25 cubic ft. capacity for the initial treatment. Thereafter, use 8 oz. perweek. Pour directly into toilet and flush. If septic tank is clogged and odorous, add 1 gallon of product directly to the tank through the manhole. VEHICLES & BOATS: Add 2 oz. per gallon of water in hold tank. Thereafter, use 1 oz. per gallon as needed. For use at a dump station, use 1 gallon per 50 gallon of tank capacity. Then use 1 pint per week for maintenance. DRAIN LINES: Use product a minimum

SPECIFICATIONS:

Boiling Range: 212

Color: Green

Detergency: Excellent

Evaporation Rate:

Flash Point: N/A

Foam Stability: Medium

Fragrance: Floral/mint

Freeze/Thaw: 3 cycles

Hard Water Tolerance: Excel-

lent

pH: 7.5+

Rinseability: Excellent

Shelf Life: 1 year

Soap Content: None

Solids: 25%

Solubility: 100%

Specific Gravity: .99

Vapor Density: >1

Vapor Pressure: 20

Viscosity: N/A

%Volatile: 75