

STRIPPED

PAINT & VARNISH REMOVER

- **NON-FLAMMABLE! * FAST ACTING**
- **EASY TO APPLY WITH BRUSH OR SPRAYER**
- **STRIPS ALL PAINTS & VARNISHES**
- **RINSES WITH WATER OR SOLVENTS**

722 STRIPPED is a super strong paint & varnish stripper. Nonflammable! Easy to use. Simply brush on and allow to work - then brush, scrape, or rinse off with water. Formulated with a balanced blend of nonflammable solvents and co-solvents along with special activators and catalysts to effectively remove paint, varnish, epoxy, polyurethane, concrete coatings, acrylics, and many other types of coatings. Contains thickening agents to cling to vertical surfaces. Has a chemical seal to prevent the evaporation of volatile solvents and blended with emulsifiers to enable easy rinsing with water.

WHERE:

HOTELS * SCHOOLS * CONSTRUCTION *
OFFICE BUILDINGS * plants * CHEMICAL
PLANTS * MUNICIPALITIES * CONTRACTORS *
HOSPITALS

FOR:

CONCRETE COATINGS * PAINT & VARNISH *
POLYURETHANE & EPOXY * ACRYLICS &
ALKYDS * WOOD & BRICK * CONCRETE &
CEMENT TILES * VERTICAL SURFACES *
FLOORS

INSTRUCTIONS

VERTICAL SURFACES: USE WITH ADEQUATE VENTILATION: Apply evenly over the surface with brush or swab. Allow to penetrate and cause the paint or coating to bubble and wrinkle. Rinse with water or scrape and brush off.

FLOORS & WALKWAYS: USE WITH ADEQUATE VENTILATION: Apply evenly over a small area at a time with brush or swab. Allow to penetrate and wrinkle coating as above. Scrape, brush or rinse with water as above. **USE OF SPRAYERS:** Product can be applied with a power

consulted to determine the compatibility of seals and gaskets with the powerful solvents in this product. Use a FACE

SPECIFICATIONS:

Boiling Range: 104+

Color: Clear

Detergency: N/A

Evaporation Rate: <1

Flash Point: N/A

Foam Stability: N/A

Fragrance: N/A

Freeze/Thaw: 3 Cycles

Hard Water Tolerance: N/A

pH: N/A

Rinseability: N/A

Shelf Life: One Year +

Soap Content: None

Solids: 5%

Solubility: Emulsifies

Specific Gravity: 1.23

Vapor Density: >1

Vapor Pressure: 304

Viscosity: 95 cts

%Volatile: 95

For Industrial Use Only