

# HYOSUNG

# 4000W

The **4000W** is a compact day safe ATM for interior use. It's ideal for smaller stores, coffee shops, bars and other locales where space is at a premium. Best of all, it serves as a hassle-free revenue generator in a reliable, secure platform. The **4000W** delivers the same high quality and proven dependability you expect from industry leader Hyosung.



## KEY FEATURES

---

### COMPACT SIZE

The **4000W** can be mounted to a wall using the sturdy steel brackets included with every ATM or optionally mounted on a table or counter-top . The **4000W** provides full set of features in a compact package and sets the standard for innovation and convenience for small spaces.

### INNOVATIVE DESIGN

The **4000W** provides unsurpassed convenience to all users by providing an intuitive graphical user interface through an 8-inch color LCD screen. The **4000W** was designed with speed and ease-of-use in mind so you get rapid transaction processing and speedy service.

### MAXIMUM RELIABILITY

Ease of maintenance and simplified service ensure maximum availability and uptime with minimal operational intervention.

### ADVANCED TECHNOLOGY

The **4000W** also supports Hyosung's advanced function applications such as Dynamic Currency Conversion and MoniView Remote Management Software.

# HYOSUNG

# 4000W

## SPECIFICATIONS

---

### DIMENSIONS

- Height: 18.8"
- Width: 25.3"
- Depth: 8.7"
- Weight: 110 lbs

### ENVIRONMENTAL

- Temperature: 41°F – 95°F  
(5°C ~ 35°C)
- Humidity: 20% – 85%

### SOFTWARE

- Microsoft Windows® CE6.0

### CUSTOMER INTERFACE

- 8" color TFT LCD
- IC Card Reader
- Anti-skimming (optional)
- Input Type – 8 function keys, PCI 5.0 compliant EPP, RKT (optional)

### MEDIA TECHNOLOGY

- 500 note cassette\*
- 20 note reject box\*
- Cashtray illumination

### SECURITY

- Electronic Lock

### PRINTER

- 2" Graphical thermal receipt printer

### ADDITIONAL INFORMATION

- Audio jack
- EPP illumination
- Retractable door handle
- Speaker
- Braille keypad
- Digital receipt
- Electronic journal
- Supports six languages: English, Spanish, French, Japanese, Chinese, & Korean
- Enhanced Standard 1 (Hyosung Standard) DCC (Dynamic Currency Conversion)
- Communication – TCP/IP
- Power Supply – AC 110-240 V, 50-60 Hz

\*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

Features and benefits are for U.S. configuration only. If located outside of the U.S., please contact sales.